

Key Features

Excellent clamping capability

Low incremental surge resistance

Typical IR less than 1μA above 12V

For surface mounted applications to optimize board space

Low profile package

Typical failure mode is short from over-specified voltage or current

Whisker test is conducted based on JEDEC JESD201A per its table 4a and 4c

IEC-61000-4-2 ESD 15kV(Air), 8kV (Contact)

ESD protection of data lines in accordance with IEC 61000-4-2 (IEC801-2)

EFT protection of data lines in accordance with IEC 61000-4-4 (IEC801-4)

Built-in strain relief

Fast response time: typically less than 1.0ps from 0V to BV min

600W peak pulse power capability at 10×1000μs waveform, repetition rate (duty cycles):0.01%

Typical maximum temperature coefficient $\Delta VBR = 0.1\% \times VBR@25^{\circ}C \times \Delta T$

Glass passivated chip junction

High temperature soldering guaranteed: 260°C/40 seconds at terminals

Plastic package has underwriters laboratory flammability 94V-O

Matte tin lead-free plated

Halogen free and RoHS compliant

Application

TVS devices are ideal for the protection of I/O Interfaces, VCC bus and other vulnerable circuits used in Telecom, Computer, Industrial and Consumer electronic applications.



Recommended For You

SMAJ12A

Littelfuse Inc
SMA

SMAJ58CA

Littelfuse Inc
SMA

SMBJ22A

Littelfuse Inc
SMB

SMAJ30A

Littelfuse Inc
SMA

SMBJ30A

Littelfuse Inc
SMB

SMAJ24CA

Littelfuse Inc
DO-214AC

SMBJ18A

Littelfuse Inc
SMB

SMBJ24A

Littelfuse Inc
SMB

SMBJ36CA

Littelfuse Inc
SMB

SMAJ12CA

Littelfuse Inc
SMA

SMCJ30CA

Littelfuse Inc
SMC

SMAJ28CA

Littelfuse Inc
SMA

SMBJ26CA

Littelfuse Inc
SMB

SMBJ17A

Littelfuse Inc
SMB

SMBJ20A

Littelfuse Inc
SMB