


**Voltage Mode PWM Controller 60V 200mA 500kHz 16-Pin
PDIP Tube**



Images are for reference only

[Inquiry](#)

Manufacturer: [Texas Instruments, Inc](#)

Package/Case: DIP-16

Product Type: Power Management ICs

RoHS: RoHS Compliant/Lead free 

Lifecycle: Active

General Description

Key Features

Fully Interchangeable with Standard UC1524 Family

Precision Reference Internally Trimmed to $\pm 1\%$

High-Performance Current Limit Function

Under-Voltage Lockout with Hysteretic Turn-on

Start-Up Supply Current Less Than 4mA

Output Current to 200mA

60V Output Capability

Wide Common-Mode Input Range for both Error and Current Limit Amplifiers

PWM Latch Insures Single Pulse per Period

Double Pulse Suppression Logic

200ns Shutdown through PWM Latch

Guaranteed Frequency Accuracy

Thermal Shutdown Protection

Description

The UC1524A family of regulating PWM ICs has been designed to retain the same highly versatile architecture of the industry standard UC1524 (SG1524) while offering substantial improvements to many of its limitations. The UC1524A is pin compatible with "non-A" models and in most existing applications can be directly interchanged with no effect on power supply performance. Using the UC1524A, however, frees the designer from many concerns which typically had required additional circuitry to solve.

The UC1524A includes a precise 5V reference trimmed to $\pm 1\%$ accuracy, eliminating the need for potentiometer adjustments; an error amplifier with an input range which includes 5V, eliminating the need for a reference divider; a current sense amplifier useful in either the ground or power supply output lines; and a pair of 60V, 200mA uncommitted transistor switches which greatly enhance output versatility.

An additional feature of the UC1524A is an under-voltage lockout circuit which disables all the internal circuitry, except the reference, until the input voltage has risen to 8V. This holds standby current low until turn-on, greatly simplifying the design of low power, off-line supplies. The turn-on circuit has approximately 600mV of hysteresis for jitter-free activation.

Other product enhancements included in the UC1524A's design include a PWM latch which insures freedom from multiple pulsing within a period, even in noisy environments, logic to eliminate double pulsing on a single output, a 200ns external shutdown capability, and automatic thermal protection from excessive chip temperature. The oscillator circuit of the UC1524A is usable beyond 500kHz and is now easier to synchronize with an external clock pulse. The UC1524A is packaged in a hermetic 16-pin DIP and is rated for operation from -55°C to $+125^{\circ}\text{C}$. The UC2524A and 3524A are available in either ceramic or plastic packages and are rated for operation from -25°C to $+85^{\circ}\text{C}$ and 0°C to 70°C , respectively. Surface mount devices are also available.

Recommended For You

UCC28064ADR

Texas Instruments, Inc

SOP16

UC3637N

Texas Instruments, Inc

DIP-18

UCC27517DBVR

Texas Instruments, Inc

SOT23-5

UCC2946IPWRQ1

Texas Instruments, Inc
TSSOP8

UCC28730QDRQ1

Texas Instruments, Inc
SOP7

UCC21222QDRQ1

Texas Instruments, Inc
SOP16

UCD9090QRGZRQ1

Texas Instruments, Inc
VQFN-48

UCC27531QDBVRQ1

Texas Instruments, Inc
SOT23-6

UCC27511AQDBVRQ1

Texas Instruments, Inc
SOT23-6

UCC2803QDRQ1

Texas Instruments, Inc
SOP8

UCC28951QPWRQ1

Texas Instruments, Inc
TSSOP24

UCC21320QDWKRQ1

Texas Instruments, Inc
SOIC-14

UCC27322QDGNRQ1

Texas Instruments, Inc
HVSSOP-8

UCC28950QPWRQ1

Texas Instruments, Inc
TSSOP24

UCC2808AQDR-2Q1

Texas Instruments, Inc
SOP8