


**I2C/SMBus Interface 100kHz/400kHz 5.5V 16-Pin TSSOP  
T/R**

Images are for reference only

[Inquiry](#)**Manufacturer:** [Texas Instruments, Inc](#)**Package/Case:** TSSOP16**Product Type:** Drivers**RoHS:** RoHS Compliant/Lead free **Lifecycle:** Active**General Description**

The TCA9534 is a 16-pin device that provides 8bits of general purpose parallel input and output (I/O) expansion for the two-line bidirectional I2C bus (or SMBus) protocol. The device can operate with a power supply voltage ranging from 1.65 V to 5.5 V, which allows for use with a wide range of devices. The device supports both 100-kHz (Standard-mode) and 400-kHz (Fast-mode) clock frequencies. I/O expanders such as the TCA9534 provide a simple solution when additional I/Os are needed for switches, sensors, push-buttons, LEDs, fans, and other similar devices.

The features of the TCA9534 include an interrupt that is generated on the INT pin. This allows the master to know when an input port changes state. The A0, A1, and A2 hardware selectable address pins allow up to eight TCA9534 devices on the same I2C bus. The device can also be reset to its default state by cycling the power supply and causing a power-on reset.

## Key Features

Low Standby Current Consumption

I2C to Parallel Port Expander

Open-Drain Active-Low Interrupt Output

Operating Power-Supply Voltage Range of 1.65V to 5.5V

5-V Tolerant I/O Ports

400-kHz Fast I2C Bus

Three Hardware Address Pins Allow up to Eight Devices on the I2C/SMBus

Input and Output Configuration Register

Polarity Inversion Register

Internal Power-On Reset

Power-Up With All Channels Configured as Inputs

No Glitch on Power Up

Noise Filter on SCL/SDA Inputs

Latched Outputs With High-Current Drive Maximum Capability for Directly Driving LEDs

Latch-Up Performance Exceeds 100 mA Per JESD 78, Class II

ESD Protection Exceeds JESD 22  
2000-V Human-Body Model (A114-A)

1000-V Charged-Device Model (C101)

## Recommended For You

---

### TCA9534PWR

Texas Instruments, Inc

TSSOP16

### TCA9517DR

Texas Instruments, Inc

SOP8

### TCA6416APWR

Texas Instruments, Inc

TSSOP24

### TCA6416ARTWR

Texas Instruments, Inc

WQFN24

### TCA4311ADGKR

Texas Instruments, Inc

MSOP-8

### TCA9554APWR

Texas Instruments, Inc

TSSOP16

### TCA9539QPWRQ1

Texas Instruments, Inc

TSSOP24

### TCA6408APWR

Texas Instruments, Inc

TSSOP16

### TCA9535DBR

Texas Instruments, Inc

SSOP24

**TCA9517DGKRQ1**

Texas Instruments, Inc  
VSSOP8

**TCA6408AQPWRQ1**

Texas Instruments, Inc  
TSSOP16

**TCA9535DBT**

Texas Instruments, Inc  
SSOP24

**TCA9803DGKR**

Texas Instruments, Inc  
MSOP8

**TCA9554ADBQR**

Texas Instruments, Inc  
SSOP16

**TCA9536DGKR**

Texas Instruments, Inc  
VSSOP-8