

## Video Proc 1.2V 0.2A 100-Pin LBGA

Manufacturer: Semtech Corporation

Package/Case: BGA100

**Product Type:** Embedded Processors & Controllers

RoHS: RoHS Compliant/Lead free

**Lifecycle:** Active



Images are for reference only

Inquiry

## **General Description**

The GS2972 is a complete SDI transmitter, generating a SMPTE 424M, SMPTE 292M, SMPTE 259M-C or DVB-ASI compliant serial digital output signal.

The integrated ClockCleaner<sup>TM</sup> allows the device to accept parallel clocks with high input jitter, and still provide a SMPTE compliant serial digital output. The device can operate in four basic user selectable modes: SMPTE mode, DVB-ASI mode, Data-Through mode, or Standby mode.

In SMPTE mode, the GS2972 performs all SMPTE processing features. Both SMPTE 425M Level A and Level B formats are supported with optional conversion from Level A to Level B for 1080p 50/60 4:2:2 10-bit.

In DVB-ASI mode, the device will perform 8b/10b encoding prior to transmission.

In Data-Through mode, all SMPTE and DVB-ASI processing is disabled. The device can be used as a simple parallel to serial converter.

The device can also operate in a lower power Standby mode. In this mode, no signal is generated at the output.

The GS2972 includes a fully SMPTE-compliant cable driver for SMPTE 259M-C, SMPTE 292M and SMPTE 424M interfaces. It features automatic dual slew-rate selection, depending on 3G-, HD- or SD-SDI operational requirements.

In accordance with SMPTE 272M and SMPTE 299M, up to eight channels (two audio groups) of serial digital audio may be embedded into the video data stream. The input audio signal formats supported by the device include AES/EBU, I2S and serial audio. 16, 20 and 24-bit audio formats are supported at 48kHz synchronous for SD modes and 48kHz synchronous or asynchronous in HD, 3Gb/s modes.

Key Features Application

Integrated audio embedder for up to 8 channels of 48kHz audio

Cameras

Integrated, low noise VCO and integrated ClockCleaner<sup>TM</sup>

Camera Control units

Integrated cable driver

Multiviewers Operation at 2.970Gb/s, 2.970/1.001Gb/s, 1.485Gb/s, 1.485/1.001Gb/s and 270Mb/s

Supports SMPTE 425M (Level A and Level B), SMPTE 424M, SMPTE 292M, SMPTE 259M-C and DVB-ASI

Ancillary data insertion Master Control Switchers

Optional conversion from SMPTE 425M Level A to Level B for 1080p 50/60 4:2:2 10-bit VTRs

Parallel data bus selectable as either 20-bit or 10-bit

Video Servers

SMPTE video processing including TRS calculation and insertion, line number calculation and insertion, line based CRC calculation and insertion, illegal code re-mapping, SMPTE 352M payload identifier generation and insertion

Encoders/Decoders

GSPI Host Interface

Up/Down/Cross Converters

1.2V digital core power supply, 1.2V and 3.3V analog power supplies, and selectable 1.8V or 3.3V I/O power supply

Audio Embedders

Low power operation (400mW typical, including cable driver)

Format Detectors
Small 11mm x 11mm 100-ball BGA package

Pb-free and ROHS compliant

Test and Measurement Equipment

Order Codes

GS2972-IBTE3: Lead-Free, RoHS Compliant, Tape and Reel-250 Pieces

GS2972-IBE3: Lead-Free, RoHS Compliant, Tray-168 Pieces

GS2972-CBE3: Lead-Free, RoHS Compliant, Tape and Reel-250 Pieces



GS2988-INE3 GS2962-IBE3 GS2970-IBE3

Semtech Corporation Semtech Corporation Semtech Corporation

QFN BGA BGA

GS2971AIBE3 GS1578ACNE3 GS2989-INE3

Semtech Corporation Semtech Corporation Semtech Corporation

BGA QFN QFN16

GS1661AIBE3 GS12281-INE3 GS12070-IBE3

Semtech Corporation Semtech Corporation Semtech Corporation

BGA100 QFN40 BGA196

GS1559-CBE2 GS2965-INE3 GS2961-IBE3

Semtech Corporation Semtech Corporation Semtech Corporation

BGA QFN BGA

GS2971-IBE3 GS6151-INIE3 GS2960-IBE3

Semtech Corporation Semtech Corporation Semtech Corporation

BGA 32-VFQFN BGA100