

TVS Diode Single Bi-Dir 30V 500W 2-Pin DO-15 T/R

Manufacturer: <u>Littelfuse Inc</u>

Package/Case: DO-15

Product Type: Thyristors

Lifecycle: Active



Images are for reference only

Inquiry

General Description

The SA Series is designed specifically to protect sensitive electronic equipment from voltage transients induced by lightning and other transient voltage events.

Key Features

Application

Typical maximum temperature coefficient $\Delta VBR = 0.1\% \times VBR @25^{\circ}C \times \Delta T$

TVS devices are ideal for the protection of I/O interfaces, VCC bus and other vulnerable circuits used in telecom, computer, industrial and consumer electronic applications.

PESD0402-140

Glass passivated chip junction in DO-15 Package

500W peak pulse capability at $10\times1000\mu s$ waveform, repetition rate (duty cycles):0.01%

Fast response time: typically less than 1.0ps from 0 Volts to BV min

Excellent clamping capability

Typical failure mode is short from over-specified voltage or current

Whisker test is conducted based on JEDEC JESD201A per its table 4a and 4c

IEC-61000-4-2 ESD 15kV(Air), 8kV (Contact).

ESD protection of data lines in accordance with IEC 61000-4-2 (IEC801-2)

EFT protection of data lines in accordance with IEC 61000-4-4 (IEC801-4)

Low incremental surge resistance

Typical IR less than 1µA above 13V

High temperature soldering guaranteed: 260°C/40 seconds / 0.375",(9.5mm) lead

length, 5 lbs., (2.3kg) tension

Plastic package has underwriters laboratory flammability classification 94V-O

Matte tin lead-free plated

SA5.0A

Halogen free and RoHS compliant

Recommended For You

Littelfuse Inc

DO-15

DO-15

SMAJ12A

Littelfuse Inc

SMAJ58CA

Littelfuse Inc

Littelfuse Inc

Littelfuse Inc

SMA

SMBJ22A

Littelfuse Inc

SMA

SMB

SA12CA

SMAJ30A SMBJ30A SMAJ24CA

Littelfuse Inc Littelfuse Inc Littelfuse Inc

SMA SMB DO-214AC

SP3010-04UTG SMBJ18A SMBJ24A

Littelfuse Inc Littelfuse Inc Littelfuse Inc

UDFN-10 SMB SMB

SMBJ36CA 5KP33A SMAJ12CA

Littelfuse Inc Littelfuse Inc Littelfuse Inc

SMB R-6 SMA