

## Full Speed USB to 1 Port RS422 Module 5V USB 1.1/USB 2.0



Images are for reference only

[Inquiry](#)

**Manufacturer:** [FTDI Chip](#)

**Package/Case:** RS-422

**Product Type:** Drivers

**RoHS:** RoHS Compliant/Lead free 

**Lifecycle:** Active

### General Description

#### Key Features

Adds one RS-422 serial port by connecting to USB

Easy plug & play installation and RS-422 device connection

Works with USB 1.1 & 2.0 Host and Hub ports

Industry standard FTDI chip set & device drivers for maximum compatibility

Microsoft Windows WHQL-certified, Mac OS X, Linux and Windows CE device drivers

Installs as a standard Windows COM port

Installs as a standard Windows COM port

FIFO with 128 byte transmit buffer, 256 byte receive buffer

RS-422 data signals: TxD+,TxD-,RxD+,RxD-,RTS+,RTS-,CTS+,CTS-,GND. Serial port speed up to 3Mbps

Powered by USB port. No external power adapter required

### Recommended For You

#### USB-COM422-PLUS4

FTDI Chip

RS-422

#### USB-COM232-PLUS2

FTDI Chip

MODULE

#### DB9-USB-D3-M

FTDI Chip

MODULE

**USB-COM485-PLUS1**

FTDI Chip

RS-422

**USB-RS485-PCBA**

FTDI Chip

MODULE

**TTL-232R-5V-PCB**

FTDI Chip

TTL-232R-5V-PCB

**VDRIVE3**

FTDI Chip

MODULE

**FT-MOD-4232HUB**

FTDI Chip

FT-MOD-4232HUB

**TTL-232R-3V3-PCB**

FTDI Chip

TTL-232R-3V3-PCB