



VFC/FVC Non-Sync 500kHz 14-Pin PDIP N Tube

Manufacturer: Analog Devices, Inc

Package/Case: 14-PDIP

Product Type: Voltage to Frequency & Frequency to

Voltage

Lifecycle: Obsolete



Images are for reference only

Inquir

General Description

TTL or CMOS compatibility is achieved in the V/F operating mode using an open collector frequency output. The pullup resistor can be connected to voltages up to 30 volts, or to +15 V or +5 V for conventional CMOS or TTL logic levels. This resistor should be chosen to limit current through the open collector output to 8 mA. A larger resistance can be used if driving a high impedance load.

Input offset drift is only 3ppm of full scale per °C, and full-scale calibration drift is held to a maximum of 100 ppm/°C (ADVFC32BH) due to a low T.C. Zener diode.

The ADVFC32 is available in commercial, industrial, and extended temperature grades. The commercial grade is packaged in a 14-pin plastic DIP while the two wider temperature range parts are packaged in hermetically sealed TO-100 cans.

Key Features

High Linearity $\pm 0.01\%$ Max at 10 kHz FS $\pm 0.05\%$ Max at 100 kHz FS $\pm 0.2\%$ Max at 500 kHz FS

Output TTL/CMOS-Compatible

V/F or F/V Conversion

6 Decade Dynamic Range

Voltage or Current Input

Reliable Monolithic Construction

MIL-STD-883-Compliant Versions Available

Recommended For You

AD7305BRZ AD9910BSVZ AD9831ASTZ

Analog Devices, Inc Analog Devices, Inc Analog Devices, Inc

SOP20 TQFP100 QFP

AD5447YRUZ

Analog Devices, Inc

TSSOP

AD537JH

Analog Devices, Inc

CAN10

AD7740YRMZ

Analog Devices, Inc

MSOP8

AD7291BCPZ

Analog Devices, Inc

LFCSP20

AD5302BRMZ

Analog Devices, Inc

MSOP10

AD652AQ

Analog Devices, Inc

DIP

AD9914BCPZ

Analog Devices, Inc

LFCSP

AD9954YSVZ

Analog Devices, Inc

QFP

AD5531BRUZ

Analog Devices, Inc

TSSOP16

AD654JN

Analog Devices, Inc

DIP8

AD73311ARSZ

Analog Devices, Inc

SSOP20

AD2S1205YSTZ

Analog Devices, Inc

LQFP44